









MODE A MODE A Automatically turns ON at dusk

WORKING MODES




Automatically turns ON to full brightness mode (800lm) when motion is detected within 6m range, and then returns to standby night glow mode (dimmed front and back light on) after 20 seconds of no



Automatically turns ON to full brightness mode (800lm) when motion is detected within 6 metre range and then returns to OFF after 30 seconds of no motion.

LUCEC® **SOLAR GUARDIAN LED WALL LIGHTS**

- Front & rear facing LED light chips provide both functional and ambient illumination
 - Perfect for outdoor entrance areas, balconies, paths, decorative garden lighting, and sheds/outhouses - No wiring, easy & simple installation



*Supplied with screws and rawl plugs



(<30 lux) and remains 160lm off

bright, up to 5 hours after which

it turns OFF.

RETAIL PACKAGING





Back light LED array Front & Rear illumination



Full & Dimmed mode

Product Specifications

CAT NO.	FINISH	FUNCTION	WORKING MODES	WATTAGE	LUMINAIRE LUMENS	COLOUR TEMP	BEAM ANGLE	INSTALL	IP	AMBIENT OPERATING TEMP	MATERIAL OF MAIN BODY	OVERALL DIMENSIONS (H, W, D)
LEXS22B30	Black	2 Modes	B,C	1.5W	220	4000K	120°	Surface	IP65	-20°C to 45°C	Polycarbonate + ABS	145 x 96 x 79mm
LEXS22W30	White	2 Modes	В,С	1.5W	220	4000K	120°	Surface	IP65	-20°C to 45°C	Polycarbonate + ABS	145 x 96 x 79mm
LEXS40B40	Black	3 Modes	A,B,C	3.2W	400	4000K	120°	Surface	IP44	-20°C to 55°C	Polycarbonate + ABS	212 x 140 x 109mm
LEXS40W40	White	3 Modes	A,B,C	3.2W	400	4000K	120°	Surface	IP44	-20°C to 55°C	Polycarbonate + ABS	212 x 140 x 109mm
LEXS80B40	Black	3 Modes	A,B,C	6.8W	800	4000K	120°	Surface	IP44	-20°C to 55°C	Polycarbonate + ABS	270 x 221 x 109mm
LEXS80W40	White	3 Modes	A,B,C	6.8W	800	4000K	120°	Surface	IP44	-20°C to 55°C	Polycarbonate + ABS	270 x 221 x 109mm

For more information contact Sales on: T: +44(0) 1952 238 100 F: +44(0) 1952 238 180 E: uk sales@luceco.uk