



Principal

Product or Component Type	Interrupor automático
Range	PowerPact P
Current Sensor Rating Range	1200 A
Rated Current	1200 A
Breaking Capacity	100 kA 240 V CA 65 kA 480 V CA 25 kA 600 V CA
AWG Gauge	AWG 3/0...500 kcmil (aluminium/copper) for 4 cable(s)
Trip Unit Technology	Electronic, ammeter, Micrologic 3.0 A, LI

Complementario

Certifications	IEC Registrado por UL CSA
Rated operational Voltage	600 V AC
Module Type	P-Frame ((*))
Mounting Location	Busbar
Mounting Mode	I-Line
Poles Description	3P
Circuit Breaker Rating Code	J
Electrical Connection	I-Line connection línea Lugs load
Continuous Current Rating	80 %
Device Short Name	A
Height	410.46 mm
Depth	204.47 mm
Width	210.06 mm
Tightening Torque	50 N.m for 95...240 mm ² (AWG 3/0...500 kcmil) 1.0...1.3 N.m

Unidades de embalaje

Paquete 1 Peso	14.515 kg
----------------	-----------

Sostenibilidad de la oferta

Estado de oferta sostenible	Producto Green Premium
Reglamento REACH	Declaración de REACH
Directiva RoHS UE	Conforme Declaración RoHS UE
Sin mercurio	Sí
Información sobre exenciones de RoHS	Sí
Normativa de RoHS China	Declaración RoHS China Producto fuera del ámbito de RoHS China. Declaración informativa de sustancias
Comunicación ambiental	Perfil ambiental del producto
Perfil de circularidad	Información de fin de vida útil
Sin PVC	Sí

Garantía contractual

Periodo de garantía	18 months
---------------------	-----------