



### Principal

Product	Interrupor automático en miniatura
Range	QOD
Current Rating	30 A
Voltage Rating	120/240 V AC 120 V AC
Mounting Type	Conexión
Number of Poles	2P
Circuit Breaker Type	Ground fault protecting class A 6 mA
Ratings	Not rated (**)
Electrical Connection	Pressure plate (**)

### Opcionales

Interrupt Rating	10 kA at 120/240 V AC 50/60 Hz 10 kA at 120 V AC 50/60 Hz
Number of Panel Spaces	2
Wire Size	AWG 14...AWG 8 copper AWG 12...AWG 8 aluminium
Tightening Torque	4.6 N.m for 2.5...10 mm <sup>2</sup> (AWG 16...AWG 14) 4.6 N.m for 4...20 mm <sup>2</sup> (AWG 12...AWG 4)
Height	105 mm
Width	38 mm
Depth	74 mm
Peso del producto	0.327 kg

### Ambiente

Certifications	Registrado por UL CSA
----------------	--------------------------

Ambient Rating	40 °C
----------------	-------

## Packing Units

Número de Unidades en el Paquete 1	1
Paquete 1 Peso	435.449 g
Paquete 1 Altura	5.842 cm
Paquete 1 ancho	9.144 cm
Paquete 1 Largo	13.462 cm

## Offer Sustainability

Estado de oferta sostenible	Producto Green Premium
Reglamento REACH	<a href="#">Declaración de REACH</a>
Directiva RoHS UE	Conforme <a href="#">Declaración RoHS UE</a>
Sin mercurio	Sí
Información sobre exenciones de RoHS	<a href="#">Sí</a>
Normativa de RoHS China	<a href="#">Declaración RoHS China</a> Producto fuera del ámbito de RoHS China. Declaración informativa de sustancias
Comunicación ambiental	<a href="#">Perfil ambiental del producto</a>
Perfil de circularidad	<a href="#">Información de fin de vida útil</a>

## Contractual warranty

Periodo de garantía	18 months
---------------------	-----------