

Ficha técnica del producto

Características

QO24L60NRNM

CENTRO DE CARGA QO Z PPALES. 60 A, 1F.
3H 2SP NEMA 3R



Principal

Marketing Trade Name	QO
Product	Load Center ((*))
Enclosure Type	Envoltorio resistente a las inclemencias del tiempo
Cover Type	Surface cover

Complementario

Tightening Torque	Main lugs: 35 lb.in, AWG 14...AWG 10, aluminium/copper Main lugs: 45 lb.in, AWG 3, aluminium/copper Main lugs 40 lb.in AWG 8...AWG 4 aluminio/cobre Main lugs: 35 lb.in, AWG 12...AWG10, aluminium/copper
Load Center Type	Fixed Mains (lugs)
Rated Current	60 A
Number of Spaces	2
Max Short Circuit Current Rating	10 kA
Maximum Number of Single Pole Circuits	4
Maximum Number of Tandem Breakers	2
Number of Phases	1 fase
Voltage Rating	120/240 V AC
Wire Size	AWG 14...AWG 4 aluminio/cobre
Electrical Connection	Lugs ((*))
Grounding Bar	Neutral (factory installed)
Electrical Connection	Lugs ((*))
Wiring Configuration	3-hilos
Busbar Material	Tin plated aluminium ((*)) embarrado eléctrico
Enclosure Material	Non-metallic
Box Number	1NM
Height	223 mm
Width	166 mm

Entorno

Enclosure Rating	NEMA 3R exterior
Ambient Air Temperature for Operation	-5 °C 40 °C
Product Certifications	Registrado por UL

Unidades de embalaje

Tipo de Unidad de Paquete 1	PCE
Número de Unidades en el Paquete 1	1
Paquete 1 Peso	649 g
Paquete 1 Altura	10.16 cm
Paquete 1 ancho	14.732 cm
Paquete 1 Largo	24.384 cm
Paquete 2 Peso	6.967 kg
Paquete 3 Peso	171.911 kg

Sostenibilidad de la oferta

Directiva RoHS UE	Bajo investigación
-------------------	--------------------

Garantía contractual

Periodo de garantía	18 months
---------------------	-----------