

Ficha técnica del producto

Características

QO2L40RB

CENTRO DE CARGA QO Z PPALES. 40 A, 1F. 3H 2SP NEMA 3R



Principal

| | |
|----------------------|---|
| Marketing Trade Name | QO |
| Product | Load Center ((*)) |
| Enclosure Type | Envolvente resistente a las inclemencias del tiempo |
| Cover Type | Surface cover |

Opcionales

| | |
|--|---|
| Tightening Torque | Main lugs: 35 lb.in, AWG 14...AWG 10, aluminium/copper Main lugs: 40 lb.in, AWG 8...AWG 4, aluminium/copper Main lugs: 35 lb.in, AWG 12...AWG10, aluminium/copper |
| Load Center Type | Fixed Mains (lugs) |
| Rated Current | 40 A |
| Number of Spaces | 2 |
| Max Short Circuit Current Rating | 65 kA |
| Maximum Number of Single Pole Circuits | 2 |
| Maximum Number of Tandem Breakers | 0 |
| Number of Phases | 1 fase |
| Voltage Rating | 120/240 V AC |
| Wire Size | AWG 14...AWG 6 copper AWG 12...AWG 6 aluminium |
| Electrical Connection | Lugs ((*)) |
| Grounding Bar | Grounding bar (ordered separately) |
| Electrical Connection | Lugs ((*)) |
| Wiring Configuration | 3-hilos |
| Busbar Material | Tin plated aluminium: busbar |
| Enclosure Material | Welded galvanized steel |
| Cover Finish | Baked enamel gris |

| | |
|------------|--------|
| Box Number | 1R |
| Height | 238 mm |
| Width | 124 mm |

Ambiente

| | |
|---------------------------------------|---------------------|
| Enclosure Rating | NEMA 3R for outdoor |
| Ambient Air Temperature for Operation | -5 °C 40 °C |
| Product Certifications | Registrado por UL |

Unidades de embalaje

| | |
|------------------------------------|-----------|
| Número de Unidades en el Paquete 1 | 1 |
| Paquete 1 Peso | 2.265 kg |
| Paquete 1 Altura | 12.192 cm |
| Paquete 1 ancho | 14.732 cm |
| Paquete 1 Largo | 27.940 cm |

Sostenibilidad de la oferta

| | |
|--------------------------------------|---|
| Estado de oferta sostenible | Producto Green Premium |
| Reglamento REACH | Declaración de REACH |
| Conforme con REACH sin SVHC | Sí |
| Directiva RoHS UE | Conforme Declaración RoHS UE |
| Sin metales pesados tóxicos | Sí |
| Sin mercurio | Sí |
| Información sobre exenciones de RoHS | Sí |
| Normativa de RoHS China | Declaración RoHS China Declaración proactiva de RoHS China (fuera del alcance legal de RoHS China) |
| Comunicación ambiental | Perfil ambiental del producto |

Garantía contractual

| | |
|---------------------|-----------|
| Periodo de garantía | 18 months |
|---------------------|-----------|