

Product data sheet

Specifications



Safety switch, heavy duty, fused, viewing window, Type 1, 600V, 200A, 3 pole

VH364

Product availability: Stock - Normally stocked in distribution facility

Price*: 1,707.00 USD

Main

| | |
|---------------------------|--|
| Product | Single Throw Safety Switch |
| Duty Rating | Heavy duty |
| Device Application | Heavy application |
| Disconnect Type | Fusible disconnect |
| Factory Installed Neutral | Field installed kit available |
| Number Of Poles | 3 |
| Current Rating | 200 A |
| Voltage Rating | 600 V AC/DC |
| Enclosure Rating | NEMA 1 steel |
| Motor Power Hp | 50 hp at 480 V AC 50-60 Hz for 3 phase motors 125 hp at 480 V AC 50-60 Hz for 3 phase motors 60 hp at 600 V AC 50-60 Hz for 3 phase motors 150 hp at 600 V AC 50-60 Hz for 3 phase motors 40 hp at 250 V DC 50 hp at 600 V DC |

Complementary

| | |
|-----------------------|---|
| Short-Circuit Current | 10 kA for H, K, J or R without fuse rejection clips 200 kA for R with fuse rejection clips 200 kA for J |
| Fuse Type | H or K R or J |
| Mounting Type | Surface |
| Electrical Connection | Lugs |
| Wiring Configuration | 3-wire |
| Wire Size | AWG 6...250 kcmil copper or aluminium |
| Tightening Torque | 275 lbf.in (31.07 N.m) 0.02...0.20 in² (13.3...127 mm²) (AWG 6...250 kcmil) |
| Depth | 8.6 in (218.44 mm) |
| Width | 16.61 in (421.89 mm) |
| Height | 28.93 in (734.82 mm) |
| Net Weight | 55.49 lb(US) (25.17 kg) |
| Grounding Kit | Field installed kit available |
| Service Entrance | Suitable service entrance for USA Suitable service entrance for Mexico |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

| | |
|----------------|----------------------|
| Certifications | UL listed file E2875 |
|----------------|----------------------|

Ordering and shipping details

| | |
|-------------------|---------------|
| Category | US10DE100008 |
| Discount Schedule | 0DE1 |
| Gtin | 3606485894348 |
| Returnability | Yes |
| Country Of Origin | US |

Packing Units

| | |
|------------------------------|------------------------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 19.38 in (49.2125 cm) |
| Package 1 Width | 8.31 in (21.1137 cm) |
| Package 1 Length | 30.00 in (76.2 cm) |
| Package 1 Weight | 54.45 lb(US) (24.7 kg) |

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency

Well-being performance

 Reach Free Of Svhc

| | |
|---------------------------|---|
| Reach Regulation | REACH Declaration |
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |