

# Product data sheet

Specifications

SQUARE D



## Safety switch, heavy duty, unfused, viewing window, NEMA 3R, 600V, 60A, 3 pole

VHU362RB

Product availability: Stock - Normally stocked in distribution facility

Price\*: 876.00 USD

### Main

Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device Application	Heavy application
Disconnect Type	Non-fusible disconnect
Factory Installed Neutral	Field installed kit available
Number Of Poles	3
Current Rating	60 A
Voltage Rating	600 V AC/DC
Enclosure Rating	NEMA 3R galvanized steel
Motor Power Hp	10 hp at 240 V AC 50/60 Hz for 1 phase motors 20 hp at 240 V AC 50/60 Hz for 3 phase motors 25 hp at 480 V AC 50/60 Hz for 1 phase motors 50 hp at 480 V AC 50/60 Hz for 3 phase motors 30 hp at 600 V AC 50/60 Hz for 1 phase motors 60 hp at 600 V AC 50/60 Hz for 3 phase motors 10 hp at 250 V DC 30 hp at 600 V DC

### Complementary

Mounting Type	Surface
Electrical Connection	Lugs
Wiring Configuration	3-wire
Wire Size	AWG 14...AWG 3 copper AWG 12...AWG 3 aluminium
Tightening Torque	50 lbf.in (5.65 N.m) (AWG 3) 45 lbf.in (5.08 N.m) (AWG 6...AWG 4) 40 lbf.in (4.52 N.m) 0.01 in <sup>2</sup> (8.367 mm <sup>2</sup> ) (AWG 8) 50 lbf.in (5.65 N.m) 0.00...0.01 in <sup>2</sup> (2.06...5.261 mm <sup>2</sup> ) (AWG 14...AWG 10)
Depth	7.038 in (178.77 mm)
Width	9.08 in (230.63 mm)
Height	18.456 in (468.78 mm)
Net Weight	15.43 lb(US) (7 kg)
Grounding Kit	Field installed kit available
Service Entrance	Suitable service entrance for USA Suitable service entrance for Mexico

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Environment

---

Certifications UL listed file E2875

## Ordering and shipping details

---

Category US10DE100009

---

Discount Schedule 0DE1

---

Gtin 3606485894669

---

Returnability Yes

---

Country Of Origin US

## Packing Units

---

Unit Type Of Package 1 PCE

---

Number Of Units In Package 1 1

---

Package 1 Height 18.75 in (47.625 cm)

---

Package 1 Width 10.38 in (26.3525 cm)

---

Package 1 Length 7.00 in (17.78 cm)

---

Package 1 Weight 17.64 lb(US) (8 kg)

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency

## Well-being performance

 Reach Free Of Svhc

---

**Reach Regulation**

[REACH Declaration](#)

---

**Eu Rohs Directive**

Compliant

[EU RoHS Declaration](#)

---

**China Rohs Regulation**

[China RoHS declaration](#)

---

**Environmental Disclosure**

[Product Environmental Profile](#)

---

**Circularity Profile**

No need of specific recycling operations

---

**California Proposition 65**

WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

---